

Glasses-Free 3D Display Datasheet

Category	Parameter	10.1"	32"	43"	55"	65"	85"
Panel	Screen Size	10.1"	32"	43"	55"	65"	85"
	Display Technology	Supports lossless gamma anti-glare display technology for realistic canvas-level rendering; Optional anti-glare eye protection display					
	Aspect Ratio	9:16	9:16	9:16	9:16	9:16	9:16
	Native Resolution	1280 × 800	1920 × 1080	1920 × 1080	1920 × 1080 (Optional 3840 × 2160)	3840 × 2160	1920 × 1080 / 3840 × 2160
	Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	Brightness	≥680 nits	≥680 nits	≥680 nits	≥680 nits	≥680 nits	≥680 nits
	Contrast Ratio	1200:1	1200:1	1200:1	1200:1	1200:1	1200:1
	Color Gamut	72% NTSC / 100% sRGB	72% NTSC / 100% sRGB	72% NTSC / 100% sRGB	72% NTSC / 100% sRGB	72% NTSC / 100% sRGB	72% NTSC / 100% sRGB
	Viewing Angle	178° (3D Depth View 60°)	178° (3D Depth View 60°)	178° (3D Depth View 60°)	178° (3D Depth View 60°)	178° (3D Depth View 60°)	178° (3D Depth View 60°)
	3D Depth Space	200 mm	200 mm	200 mm	300 mm	300 mm	500 mm
	Response Time	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)
	Surface Treatment	Anti-Glare Glass (Haze 25%)	Anti-Glare Glass (Haze 25%)	Anti-Glare Glass (Haze 25%)	Anti-Glare Glass (Haze 25%)	Anti-Glare Glass (Haze 25%)	Anti-Glare Glass (Haze 25%)
Mechanical	Cabinet Color	Black					
	Active Area (W×H)	140 × 224 mm	376.3 × 669 mm	504.2 × 896.4 mm	644.3 × 1145.4 mm	806.4 × 1432.9 mm	1058.5 × 1881.7 mm
	Enclosure Material	Front: Narrow Metal Bezel; Rear: Metal Back Cover					
	Mounting	Desktop Stand / Wall Mount (Optional)	Wall Mount / Floor Stand (Optional)	Wall Mount / Floor Stand (Optional)	Wall Mount (VESA 400 × 200 mm) / Floor Stand (Optional)	Wall Mount (VESA 400 × 200 mm) / Floor Stand (Optional)	Wall Mount (VESA 400 × 200 mm) / Floor Stand (Optional)
Environment	Operating Temperature	0 °C – 25 °C					
	Operating Humidity	20% – 80% RH					
Power	Power Input	AC 100 – 240 V ~, 50/60 Hz					
	Power Supply Type	Built-in PSU (Internal)					
Power Consumption	Standby Mode	≤2 W					
Accessories	Standard Accessories	Remote Control, Power Cord, HDMI Cable, User Manual (EIG, IG)					