

Outdoor Floor Standing Display - Type B Datasheet

Category	Parameter	43"	55"	65"	75"
Panel	Screen Size	43"	55"	65"	75"
	Panel Technology	ADS	IPS	IPS	IPS
	Backlight Technology	Direct	Direct	Direct	Direct
	Aspect Ratio	16:9	16:9	16:9	16:9
	Native Resolution	1920 × 1080	3840 × 2160	3840 × 2160	3840 × 2160
	Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz
	Brightness	3000 nits	3000 nits	3000 nits	3000 nits
	Contrast Ratio	1200:1	1200:1	1200:1	1200:1
	Color Gamut	98% sRGB	73% NTSC	68% NTSC	69% NTSC
	Viewing Angle	178° × 178° (H/V)	178° × 178° (H/V)	178° × 178° (H/V)	178° × 178° (H/V)
	Response Time	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)
	Surface Treatment	Anti-Glare / Matte Finish (AGLR)	Anti-Glare / Matte Finish (AGLR)	Anti-Glare Glass (Haze 3%)	Anti-Glare Glass (Haze 3%)
	Operating Hours	24/7	24/7	24/7	24/7
Connectivity	Input	HDMI, USB × 2			
Mechanical	Cabinet Color	Black			
	Dimensions (W×H×D)	533 × 1600 × 180 mm	801 × 1700 × 180 mm	924 × 1900 × 180 mm	1049 × 2122 × 200 mm
	Net Weight	100 kg	150 kg	200 kg	260 kg
Key Features	Key Features	Support In-depth System Customization			
Environment	Operating Temperature (No Direct Sunlight)	0 °C – 40 °C			
	Operating Temperature (Direct Sunlight)	0 °C – 30 °C (Cooling system recommended for outdoor use)			
	Operating Humidity	10% – 80% RH			
Power	Power Input	AC 100 – 240 V ~, 50/60 Hz			
	Power Supply Type	Built-in PSU (Internal)			
Power Consumption	Typical	≤250 W	≤350 W	≤430 W	≤500 W
	Off Mode	≤0.5 W	≤0.5 W	≤0.5 W	≤0.5 W
Audio	Built-in Speakers	5 W × 2			
Language	OSD Language	Multi-language (Chinese, English, etc.)			
Accessories	Standard Accessories	Remote Control, Power Cord, HDMI Cable, User Manual (EIG, IG), IR Receiver (Ambient Light Sensor)			